



**PRO|EDGE™**  
Thin Clients  
For IBM® Host Connectivity

## **5-Year Warranty** Best Warranty in the Industry

For 30 years, I-O Corporation has been known in the IT community for providing customers with highly reliable products. With that legacy, I-O's ProEdge thin clients offer the peace of mind of a 5-year warranty. Not only is ProEdge reliable, it is *Small, Simple and Secure*.



## **Small** Footprint and Total Cost of Ownership

With dimensions that are about the size of a three CD set, **ProEdge** occupies a small space on a desktop. Despite its small size, **ProEdge** offers the flexibility of XPe, CE, and Linux operating systems and the convenience of wireless connectivity.

In addition to having a small price tag, **ProEdge** thin clients save time and money by allowing the system administrator to configure, manage, and update each workstation from a central location.

## **Simple** to Manage and Deploy

To make things really simple, **ProEdge** offers Symantec's™ Altiris® Deployment Solution™. As a leading client management tool, Altiris provides console and web-based control, reporting, alerting, policy driven software delivery, patch management, and other Altiris lifecycle management solutions.

## **Secure** ProEdge Thin Clients

With I-O's Endpoint Security Software, an IT manager has the option to remotely disable access to any USB mass storage device attached to an XPe **ProEdge** thin client. This security advantage prevents employees from introducing unauthorized or dangerous files to the network and protects sensitive information from being copied.

With three decades of experience in display technology, I-O Corporation continues its commitment to excellence by offering powerful thin clients that are *small, simple, and secure*.



Altiris Solutions  
VERIFIED





# PRO | EDGE™

Thin Clients  
For IBM® Host Connectivity

## Specifications & Features

### Base Models HARDWARE

	ProEdge HC5	ProEdge HC8	ProEdge HC15	ProEdge HX8	ProEdge HX15
Operating System	CE 5.0	CE 5.0	CE 5.0	XPE	XPE
Processor	AMD Geode™ GX533	AMD Geode™ LX800	VIA C7 1.5 GHz	AMD Geode™ LX800	VIA C7 1.5 GHz
Ram	128 MB	128 MB	256 MB	256 MB	512 MB
Ram Upgrade (Up to)	NA	1 GB	1 GB	1 GB	1 GB
Flash	64 MB	64 MB	64 MB	512 MB	1 GB
Flash Upgrade (Up to)	8 GB	8 GB	8 GB	8 GB	8 GB
Video Port	DB 15	DB 15	VGA	DB 15	DVI
Display Resolution (Up to)	1600x1200	1920x1440	1920x1200	1920x1440	1920x1200
USB Ports	2 rear*, 2 front*	2 rear, 2 front	2 rear, 2 front	2 rear, 2 front	2 rear, 2 front
Ethernet	10/100	10/100	10/100	10/100	10/100
Microphone Port	✓	✓	✓	✓	✓
Speaker Port	✓	✓	✓	✓	✓
Mouse	✓	✓	✓	✓	✓
104 Key Keyboard	Optional	Optional	Optional	Optional	Optional
122 Key Keyboard	Optional	Optional	Optional	Optional	Optional
Wireless	NA	Optional	Optional	Optional	Optional
LCD Mounting Bracket	Optional	Optional	Optional	Optional	Optional
USB to Serial Adapter	Optional	Optional	Optional	Optional	Optional
USB to Parallel Adapter	Optional	Optional	Optional	Optional	Optional
USB Dual Monitor Adapter	NA	NA	NA	Optional	Optional

\*USB Type 1.1

### SOFTWARE

IBM 5250 Display Emulations	✓	✓	✓	✓	✓
IBM 5250 SCS Printer Emulations	✓	✓	✓	✓	✓
IBM 3270 SCS Printer Emulations	NA	NA	NA	✓	✓
Terminal Emulation Suite	✓	✓	✓	✓	✓
RDP 5.x/ICA 9.x	✓	✓	✓	✓	✓
I-O Configuration Utility	✓	✓	✓	✓	✓
Altiris Client†	Optional	Optional	Optional	Optional	Optional
Browser and E-mail	Optional	Optional	Optional	✓	✓
Viewers	Optional	Optional	Optional	Downloadable	Downloadable

†Requires Altiris Deployment Solution v 6.8 (build 282) or newer.

### ENVIRONMENT

#### AC/DC adapter

Input All Models: 90-240 VAC,  
50/60 Hz  
Output HC5, HC8, & HX8:  
12VDC, 1.2A  
Output HC15, & HX15:  
12 VDC, 3.5 A

#### Wireless Option

HC5: 802.11 b/g USB  
HC8, & HC15: 802.11 b/g  
HX8, & HX15: 802.11 a/b/g

#### Dimensions

HC5, HC8, & HX8: 1.5x6x5.3 in  
HC15, & HX15: 1.7x5.5x5.1 in

#### Weight

HC5, HC8, & HX8: .8 lbs  
HC15, & HX15: 1.2 lbs

#### Operating Temp

All Models: 10°-30° C, 50°-90° F

#### Humidity

All Models: 0-90% non-condensing

#### Regulatory:

FCC Class A, CE, RoHS



## Features & Benefits

- **5-Year Warranty:** Offers longevity, investment protection and peace of mind.
- **Multi-Host Support:** System i5, iSeries, AS/400, IBM mainframes, Unix and Windows data input and retrieval can be accomplished through one display station.
- **5250 Keyboards:** True IBM 122-key 5250 keyboard layout makes the transition from dedicated 5250 terminals easy while still providing full Windows support.
- **Flexibility:** Offers a choice of operating systems (Linux, CE and XPe), processor speeds, memory sizes and more.
- **Total Cost of Ownership:** Economical to manage and support. Low power consumption and heat output.
- **Wireless Option:** ProEdge offers the flexibility of wireless 802.11 connectivity.
- **Managed by Altiris:** Provides a comprehensive central client management tool that offers control, reporting, alerting, policy driven software delivery, patch management, and more.
- **USB Management:** An IT manager can remotely disable access to all USB mass storage devices, preventing unauthorized files from being introduced to the network. In addition, confidential files cannot be copied.
- **Small Footprint:** Occupies a small amount of valuable desktop space. Mountable on the back of a VESA standard LCD monitor.
- **TN5250e/TN3270e Printing Emulation:** ProEdge allows IBM host print jobs to be printed quickly and accurately with full printing control – host print jobs are not lost in the “black hole” of Ethernet printing.